

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 11/12/2023

Reviewed on 11/12/2023

1 Identification

- **Product Identifier**
- **Trade Name: Timesaver Lapping Compound - Yellow Label for Soft Metals (40N, 60N, 80N, 100N)**
- **Product Number:** 40N, 60N, 80N, 100N
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product Description:**
Obtaining precision finishes on machined components.
Use pattern: professional use; consumers.
- **Uses advised against** No restrictions on use known.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
Micro Surface Corporation
270 Hillsdale Avenue
San Jose, CA, U.S.A. 95136
Website: www.ws2coating.com
Email: info@ws2coating.com
(408) 723-0700
- **Emergency telephone number:** (408) 723-0700

2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Health hazard

Carcinogenicity 1A

H350 May cause cancer.

Specific Target Organ Toxicity - Repeated Exposure 1

H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.



Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3

H335 May cause respiratory irritation.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Danger
- **Hazard-determining components of labeling:**
Quartz (SiO₂)
Sodium dodecylbenzenesulphonate
- **Hazard statements:**
H319 Causes serious eye irritation.
H350 May cause cancer.
H335 May cause respiratory irritation.
H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 11/12/2023

Reviewed on 11/12/2023

Trade Name: Timesaver Lapping Compound - Yellow Label for Soft Metals (40N, 60N, 80N, 100N)

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values. 20 % of the mixture consists of component(s) of unknown toxicity.

Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)



Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

Chemical characterization: Substance

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous Components:

CAS: 14808-60-7 RTECS: VV 7330000	Quartz (SiO ₂) ☠ Carcinogenicity 1A, H350; Specific Target Organ Toxicity - Repeated Exposure 1, H372; ⚠ Acute Toxicity - Inhalation 4, H332; Specific Target Organ Toxicity - Single Exposure 3, H335; Eye Irritation 2B, H320	45-50%
CAS: 7727-43-7 RTECS: CR 0600000	barium sulphate, natural	30-40%
CAS: 25155-30-0	Sodium dodecylbenzenesulphonate ⚠ Acute Toxicity - Inhalation 3, H331; ⚠ Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335; Flammable Liquids 4, H227	5-9%

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 11/12/2023

Reviewed on 11/12/2023

Trade Name: Timesaver Lapping Compound - Yellow Label for Soft Metals (40N, 60N, 80N, 100N)

CAS: 7757-82-6

Sodium Sulphate

5-10%

Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

Description of first aid measures

General information: If symptoms persist, call a physician.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in the side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.

After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor. If easy to do so, remove contact lenses if worn. If eye irritation occurs, consult a doctor.

After swallowing:

Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. If swallowed and symptoms occur, consult a doctor.

Information for doctor**Most important symptoms and effects, both acute and delayed:**

Quartz: Can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death; inhaled from occupational sources is classified as carcinogenic to humans. Some studies show in workers exposed to respirable quartz excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease, chronic bronchitis and emphysema.

Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

Extinguishing media**Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

For safety reasons unsuitable extinguishing agents: No further relevant information.

Special hazards arising from the substance or mixture:

Toxic fumes and carbon monoxide.

In the event of fire the following can be released: Sulphur oxides; Carbon oxides; Sodium oxides; hydrogen sulphide.

Advice for firefighters Use water spray to cool unopened containers.

Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 11/12/2023

Reviewed on 11/12/2023

Trade Name: Timesaver Lapping Compound - Yellow Label for Soft Metals (40N, 60N, 80N, 100N)

- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.
Dispose of the collected material according to regulations.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

· PAC-1:		
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
7727-43-7	barium sulphate, natural	15 mg/m ³
7757-82-6	Sodium Sulphate	9.8 mg/m ³
25155-30-0	Sodium dodecylbenzenesulphonate	2.1 mg/m ³
· PAC-2:		
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
7727-43-7	barium sulphate, natural	170 mg/m ³
7757-82-6	Sodium Sulphate	110 mg/m ³
25155-30-0	Sodium dodecylbenzenesulphonate	23 mg/m ³
· PAC-3:		
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
7727-43-7	barium sulphate, natural	990 mg/m ³
7757-82-6	Sodium Sulphate	650 mg/m ³
25155-30-0	Sodium dodecylbenzenesulphonate	87 mg/m ³

7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**
Avoid breathing fume/gas/mist/vapors/spray.
Keep receptacles tightly sealed.
Keep container closed with cap when not in use.
Open and handle receptacle with care.
Keep out of reach of children.
Avoid creating and breathing dust/fume/gas/mist/vapors/spray.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool, dry place in tightly closed receptacles.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** Obtaining precision finishes on machined components.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 11/12/2023

Reviewed on 11/12/2023

Trade Name: Timesaver Lapping Compound - Yellow Label for Soft Metals (40N, 60N, 80N, 100N)

· **Control parameters:**

· **Components with occupational exposure limits:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituents have no known exposure limits.

14808-60-7 Quartz (SiO₂)	
PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *respirable particulate matter, A2
7727-43-7 barium sulphate, natural	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 5* mg/m ³ *inhalable fraction; E
7757-82-6 Sodium Sulphate	
TLV	Short-term value: NIC-0.2 mg/m ³ thoracic fraction of aerosol

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment**

· **General protective and hygienic measures:**

Ensure that eyewash stations and safety showers are close to the workstation location.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.



NIOSH/OSHA approved breathing apparatus.

· **Protection of hands:**



Protective gloves

· **Material of gloves:**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary and ensure during use that the gloves are still retaining their protective properties.

· **Penetration time of glove material:** Not applicable.

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 11/12/2023

Reviewed on 11/12/2023

Trade Name: Timesaver Lapping Compound - Yellow Label for Soft Metals (40N, 60N, 80N, 100N)

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

· **Limitation and supervision of exposure into the environment:** None

9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Powder
Color:	Yellow
Odor:	Odorless
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	≥2,230 °C (≥3630 °F)

Flash point:	None
Flammability (solid, gaseous):	Not determined.
Auto igniting:	Not applicable
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not self-igniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure:	Not applicable.
Density:	2.3 g/cm ³ (19.1935 lbs/gal)
Relative density:	Not determined.
Vapor density:	Not applicable.
Evaporation rate:	Not applicable.
Solubility in / Miscibility with:	
Water:	Insoluble.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not applicable.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 11/12/2023

Reviewed on 11/12/2023

Trade Name: Timesaver Lapping Compound - Yellow Label for Soft Metals (40N, 60N, 80N, 100N)

- Kinematic:** Not applicable.
- Solvent content:**
- VOC content:** 0.00 %
- Solids content:** 100.0 %
- Other information:** No further relevant information available.

10 Stability and Reactivity

- Reactivity:** No further relevant information available.
- Chemical stability:** Product is stable under normal conditions.
- Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- Possibility of hazardous reactions:** No dangerous reactions known.
- Conditions to avoid:**
 - Dust generation.
 - Incompatible Materials
- Incompatible materials:**
 - Strong oxidizing agents.
 - Strong acids
 - Contact with fluorine, oxygen difluoride, and chlorine trifluoride will cause fire.
- Hazardous decomposition products:**
 - Burning produces obnoxious and toxic fumes. In the event of fire the following can be released: Sulphur oxides; Carbon oxides; Sodium oxides; hydrogen sulphide.

* 11 Toxicological Information

- Information on toxicological effects:**
- Acute toxicity:**

LD/LC50 values that are relevant for classification:

14808-60-7 Quartz (SiO₂)

Oral	LD50	>22,500 mg/kg (Rat) mg/kg (rabbit)
Inhalative	LC50/96 hours	1,033 mg/l (Trout)

25155-30-0 Sodium dodecylbenzenesulphonate

Oral	LD50	438 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/96 hours	3.2 mg/l (Cyprinodon variegatus (minnow))

- Primary irritant effect:**
- On the skin:** Irritant to skin and mucous membranes.
- On the eye:** Irritating effect.
- Sensitization:** No data available.
- Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - Irritant

Carcinogenic categories:

IARC (International Agency for Research on Cancer):

"In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 11/12/2023

Reviewed on 11/12/2023

Trade Name: Timesaver Lapping Compound - Yellow Label for Soft Metals (40N, 60N, 80N, 100N)

activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicate dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled"

14808-60-7	Quartz (SiO ₂)	1
------------	----------------------------	---

· **NTP (National Toxicology Program):**
None of the ingredients are listed.

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration):**
None of the ingredients are listed.

None of the ingredients are listed.		
-------------------------------------	--	--

12 Ecological Information

· **Toxicity:**

· Aquatic toxicity:		
14808-60-7 Quartz (SiO₂)		
EC50	218 mg/l (Green algae)	
7757-82-6 Sodium Sulphate		
EC50	2,564 mg/l (Water flea)	

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment:**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household waste. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

· **Uncleaned packaging**

· **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 11/12/2023

Reviewed on 11/12/2023

Trade Name: Timesaver Lapping Compound - Yellow Label for Soft Metals (40N, 60N, 80N, 100N)

14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **UN proper shipping name:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Transport hazard class(es):**
- **DOT, ADR/ADN, ADN, IMDG, IATA**
- **Class:** Non-Regulated Material
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **UN "Model Regulation":** Non-Regulated Material

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

7727-43-7 barium sulphate, natural

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients are listed.

· **California Proposition 65:**



WARNING: This product can expose you to chemicals including the listed chemicals which are known to the State of California to cause cancer, birth defects and/or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

· **Chemicals known to cause cancer:**

14808-60-7 Quartz (SiO₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **New Jersey Right-to-Know List:**

14808-60-7 Quartz (SiO₂)

7727-43-7 barium sulphate, natural

25155-30-0 Sodium dodecylbenzenesulphonate

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 11/12/2023

Reviewed on 11/12/2023

Trade Name: Timesaver Lapping Compound - Yellow Label for Soft Metals (40N, 60N, 80N, 100N)

· New Jersey Special Hazardous Substance List:		
14808-60-7	Quartz (SiO ₂)	CA
· Pennsylvania Right-to-Know List:		
14808-60-7	Quartz (SiO ₂)	
7727-43-7	barium sulphate, natural	
7757-82-6	Sodium Sulphate	
· Pennsylvania Special Hazardous Substance List:		
7757-82-6	Sodium Sulphate	E
· Carcinogenic categories:		
· EPA (Environmental Protection Agency):		
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
· TLV (Threshold Limit Value established by ACGIH):		
14808-60-7	Quartz (SiO ₂)	A2
· NIOSH-Ca (National Institute for Occupational Safety and Health):		
14808-60-7	Quartz (SiO ₂)	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



· Signal word: Danger

· Hazard-determining components of labeling:

Quartz (SiO₂)
Sodium dodecylbenzenesulphonate

· Hazard statements:

H319 Causes serious eye irritation.
H350 May cause cancer.
H335 May cause respiratory irritation.
H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

· Precautionary statements:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a poison center/doctor if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 11/12/2023

Reviewed on 11/12/2023

Trade Name: Timesaver Lapping Compound - Yellow Label for Soft Metals (40N, 60N, 80N, 100N)

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **Contact:**

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety and Health
OSHA: Occupational Safety & Health Administration
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flammable Liquids 4: Flammable liquids – Category 4
Acute Toxicity - Inhalation 3: Acute toxicity – Category 3
Acute Toxicity - Inhalation 4: Acute toxicity – Category 4
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B
Carcinogenicity 1A: Carcinogenicity – Category 1A
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106