




Key-type drill chucks with key, DIN ISO 10887

With taper mounting respectively thread mounting impact resistant. For drills with a high frequency we recommend key-type drill chuck Prima-Mat.

Technical features:

- the versatile applicable model has proven itself for decades, especially on hand-operated drilling machines and impact drilling machines
- if required, we deliver the heavy industrial chucks with DIN-taper in the sizes 6-10 with draw-off thread, in the sizes 13-20 with driver

Tool group A01
Type 111 **Prima**
heavy industrial version for stationary and hand-operated percussion drilling machines



| Item no. | Size | Clamping capacity | Mount | External Ø | Length opened | Length closed | Key size |
|------------------------|------|-------------------|---------|------------|---------------|---------------|----------|
| 072810 ● | 6 | 0,5-6,5 | J1 | 29,5 | 42,5 | 52,5 | S1 |
| 245548 ● | 6 | 0,5-6,5 | B12 | 29,5 | 47,5 | 57,5 | S1 |
| 1033093 ● | 7 | 0,5-7 | B10 | 23,7 | 39 | 48,3 | S1 |
| 072628 ● | 8 | 0,5-8 | 3/8"-24 | 34,5 | 49,5 | 61 | S2 A |
| 072631 ● | 8 | 0,5-8 | 1/2"-20 | 34,5 | 49,5 | 61 | S2 A |
| 072656 ● | 8 | 0,5-8 | J1 | 34,5 | 48 | 58,5 | S2 A |
| 245549 ● | 8 | 0,5-8 | B12 | 34,5 | 50 | 60,5 | S2 A |
| 064524 ● | 10 | 1-10 | 1/2"-20 | 42,8 | 59 | 74 | S2 A |
| 072687 ● | 10 | 1-10 | B16 | 42,8 | 63 | 77 | S2 A |
| 072693 ● | 10 | 1-10 | J2 | 42,8 | 59 | 75,5 | S2 A |
| 072812 ● | 10 | 1-10 | M18x2,5 | 42,8 | 65 | 80 | S2 A |
| 072815 ● | 13 | 1-13 | B16 | 52 | 67,5 | 86 | S3 |
| 072818 ● | 13 | 1-13 | J6 | 52 | 67,5 | 86 | S3 |
| 072819 ● | 13 | 1-13 | J33 | 52 | 67,5 | 86 | S3 |
| 072820 ● | 13 | 1-13 | 5/8"-16 | 52 | 68,5 | 87,5 | S3 |
| 072821 ● | 13 | 1-13 | M18x2,5 | 52 | 74,5 | 93,5 | S3 |
| 072825 ● | 16 | 1-16 | B18 | 56,5 | 79 | 98 | S3 |
| 072827 ● | 16 | 1-16 | J3 | 56,5 | 79 | 98 | S3 |
| 072828 ● | 16 | 1-16 | J6 | 56,5 | 79 | 98 | S3 |
| 072829 ● | 16 | 1-16 | 5/8"-16 | 56,5 | 80 | 100,5 | S3 |
| 072831 ● | 20 | 5-20 | B22 | 65 | 92,5 | 113,5 | S4 |
| 072833 ● | 20 | 5-20 | J3 | 65 | 82,5 | 103,5 | S4 |
| 072834 ¹⁾ ● | 26 | 5-26 | B24 | 80 | 120 | 147 | S4 |

¹⁾ with driver

