









BEAR PAW









PERMANENT TYPE MAGNET---
NEEDS NO RECHARGING

MAGNETIC HANDLES

Model 100 	Wt. 4 lbs. Maximum Lift 100 lbs. Maximum Magnetic Penetration 1/8"	Model 150 	Wt. 6 lbs. Maximum Lift 150 lbs. Maximum Magnetic Penetration 1/16"
Model 250 	Wt. 6 lbs. Maximum Lift 250 lbs. Maximum Magnetic Penetration 1/16"	Model 400 	Wt. 8 lbs. Maximum Lift 400 lbs. Maximum Magnetic Penetration 1/8"
Model 600 	Wt. 10 lbs. Maximum Lift 600 lbs. Maximum Magnetic Penetration 1/8"	Model 600 CA 	Wt. 12 lbs. Maximum Lift 600 lbs. Maximum Magnetic Penetration 1/8"

MAGNETIC ANGLE

OUTSIDE ANGLES		INSIDE ANGLES	
B-41		B-40	
	$1\frac{1}{4}'' \times 7\frac{1}{4}'' \times 10\frac{1}{2}''$ WT. 3½ lbs.		$1\frac{1}{4}'' \times 6\frac{3}{8}'' \times 6\frac{3}{8}''$ WT. 3 lbs. A QUICK METHOD FOR HOLDING A RIGHT ANGLE WITH PLATE OR SHEET STEEL
B-81		B-80	
	$2'' \times 7\frac{1}{4}'' \times 10\frac{1}{2}''$ WT. 5 lbs.		$2'' \times 6\frac{3}{8}'' \times 6\frac{3}{8}''$ WT. 4½ lbs.
ADJUSTABLE ANGLES HAVE BUILT IN PROTRACTOR			
B-40A		B-80A	
	$1\frac{1}{4}'' \times 7\frac{1}{2}'' \times 7\frac{1}{2}''$ WT. 3 lbs.		$2'' \times 7\frac{3}{4}'' \times 7\frac{3}{4}''$ WT. 5 lbs. A QUICK METHOD FOR HOLDING FROM 45° TO 90° ANGLE WITH PLATE OR SHEET STEEL

MODEL B-40s

APPROX. 50 LBS. HOLDING FORCE PER FACE

MODEL B-80s

APPROX. 100 LBS. HOLDING FORCE PER FACE

DRILL JIG

A MUST . . . FOR ANY DRILL PRESS!
INSTANT SET-UP FOR POSITION DRILLING

Dimensions: 7½" x 4¾" Weight: 3 lbs



NO WIRES! NO BATTERY! NO ELECTRICITY!
NO DRILL BREAKAGE caused by lateral movement!

GUN CHUCK



2½" x 3" x 5½"

Weight: 1½ lbs.

HOLDS FLAT PARTS FOR SANDING,
POLISHING, GRINDING, TACK WELDING

**Most powerful tool, for
its size, ever made!**

. . . one of the most useful tools ever seen!

MODEL 50 MAGNETIC BLOCK

FOR HOLDING JIGS AND FIXTURES TO STEEL TABLES



2½" x 2½" x 1½"

Weight: 1 lb.

Capacity: 50 lbs.

HAS ¼" 20 TAPPED HOLE CENTER TOP OF BLOCK

BEAR PAW



CRANE ASSEMBLY MODEL 600 CA



600 CRANE ASSEMBLY SPECIFICATIONS

LIFTING CAPACITY---TESTED IN EXCESS OF 600 POUNDS

EYE BOLT INSIDE DIAM.---1¼"

DIMENSIONS---6" x 7⅛", OVERALL HEIGHT 4½"

WEIGHT---10 POUNDS APPROX.

PROVEN USEFUL FOR HANDLING DIES DRILL JIGS, AND MACHINE FIGURES AND STEEL PLATE
CAM ACTION HANDLE EASILY BREAKS MAGNETIC CIRCUIT. MUST BE USED ON FLAT SURFACES.

MAGNETIC FISHING TOOLS

FOR DRILLERS OF BLAST HOLES - WATER WELLS - EXPLORATIONS - ETC.

PERMANENT TYPE MAGNETS - NEED NO RECHARGING

THE MAGNETIC FIELD IS DIRECTED OUT OF THE BOTTOM OF THE TOOL

NO MAGNETISM ON THE SIDES - THUS IT WILL NOT ADHERE TO THE CASING



*GUIDELINE OF CAPACITY ON A CLEAN, FLAT SURFACE

Size	Cap.	Wt.
3½	150#	7 lb.
4½	350#	12 lb.
5½	600#	16 lb.
6½	800#	21 lb.

INSIDE DIAMETER OF EYEBOLT-1¼"

CAPACITY DEPENDS ON THE SURFACE AREA OF CONTACT WITH THE ITEM BEING FISHED.

*AN ASSURED CAPACITY IS NOT FEASIBLE EXCEPT ON A FLAT, CLEAN SURFACE OF ¼" OR THICKER

Bar Type Magnet

A THOUSAND AND ONE USES SUCH AS COLLECTING METAL PARTICLES OUT OF TANKS- i.e.: OIL-COOLING, COLLECTING STEEL CUTTINGS AROUND DRILL PRESSES, MILLING MACHINES, GRINDERS, DUST COLLECTORS, ETC.

THREE SIZES ARE PRESENTLY STANDARD WITH A ¼" HOLE SPACED ¾" FROM ONE END FOR HANGING OR MOUNTING.

5/8"x1 ¼"x12" LONG

5/8"x1 ¼"x14" LONG

5/8"x1 ¼"x18" LONG

OTHER LENGTHS CAN BE MADE TO ORDER, RANGING FROM 3" TO 48" IN LENGTH.

REPLACEMENT PARTS

SPRINGS -- HANDLE KITS -- HANDLE PINS

MADE IN USA

Newman Tools Inc.
185 Iber Rd.
Ottawa, Ontario, Canada K2S 1E7
Tel 613-836-6776 Fax 613-836-9070